

500mA、微功率、VLDO线性稳压器**UM1770Y-xx SOT89-5****UM1770DA-xx DFN6 2.0×2.0****UM1770S-xx SOT23-5****描述**

UM1770系列是专为低功耗便携式应用设计的超低压差(VLDO)线性稳压器。UM1770系列典型输出噪声仅为 $90\mu\text{V}_{\text{RMS}}$ (固定输出, $V_{\text{OUT}}=1.0\text{V}$), 且最大压差在500mA的负载电流条件下仅为320mV。内部P沟道MOSFET传输晶体管无需基极电流驱动, 因此在最大负载电流为500mA时, 该器件正常工作时只消耗250 μA 电流。

其他特点包括高输出电压精度、卓越的瞬态响应、欠压锁定、采用超低ESR陶瓷电容 (低至1 μF) 时的稳定性、短路和过热过载保护以及输出电流限制。

UM1770Y-xx系列采用SOT89-5封装, UM1770DA-xx系列采用扁平DFN6 2.0×2.0封装, UM1770S-xx系列采用SOT23-5封装。

应用











- 蓝牙/802.11 板卡
- PDA 和笔记本电脑
- 便携式仪器和电池供电系统
- 蜂窝电话


特性

- 超低压差: 500mA 负载电流下最大 320mV
- 最大输入电压: 6.0V
- 低噪声: (10Hz 至 100kHz)
 $90\mu\text{V}_{\text{RMS}}$ (固定输出, $V_{\text{OUT}}=1.0\text{V}$);
 $60\mu\text{V}_{\text{RMS}}$ (可调输出, $V_{\text{OUT}}=1.0\text{V}$);
 $194\mu\text{V}_{\text{RMS}}$ (可调输出 $V_{\text{OUT}}=3.3\text{V}$);
 $305\mu\text{V}_{\text{RMS}}$ (可调输出, $V_{\text{OUT}}=5.0\text{V}$)
- 电压准确度: $\pm 2\%$ (500mA 时)
- 快速瞬态响应
- 欠压锁定
- UM1770Y/DA/S-xx 的固定输出电压范围为 1.0V 至 4.0V, 电压步径为 0.1V
- UM1770Y/DA/S-00 的可调输出电压范围为 1.0V 至 5.0V
- 输出电流限制
- 采用 1 μF 的电容时输出保持稳定
- 过热过载保护和短路保护
- 扁平 SOT89-5、DFN6 2.0×2.0 和 SOT23-5 封装

Pin Configurations

Top View

(Top View) 	 Marking PIN1 M: Month Code UM1770DA-xx DFN6 2.0×2.0
(Top View) 	 Marking PIN1 M: Month Code UM1770DA-00 DFN6 2.0×2.0
	 XX: Week Code UM1770Y-xx SOT89-5
	 XX: Week Code UM1770Y-00 SOT89-5
	 M: Month Code UM1770S-xx SOT23-5



* The tab on the bottom of the package enhances thermal performance and is electrically connected to GND (substrate level). It is recommended that the tab be connected to the ground plane on the board. If not, the tab can be left open.

Pin Description

Pin Number (Fixed V _{OUT})			Pin Number (Adjustable V _{OUT})			Symbol	Function
DFN6 2.0×2.0	SOT 89-5	SOT 23-5	DFN6 2.0×2.0	SOT 89-5	SOT 23-5		
1	3	3	1	3	3	SHDN	Shutdown Input: High=Activate LDO, Low=Shutdown LDO
2	2	2	2	2	2	GND	Ground
3	4	1	3	4	1	VIN	Power Supply
4	5	5	4	5	5	VOUT	Voltage Regulated Output
5, 6	1	4	5	-	-	NC	Not Connected
-	-	-	6	1	4	FB	Output Voltage Feedback

Naming Information

UM1770□□-□□

00: Adjustable Output Voltage
Fixed Output Voltage
10: 1.0V
11: 1.1V
12: 1.2V
.....
40: 4.0V
Package Type
Y: SOT89-5
DA: DFN6 2.0×2.0
S: SOT23-5

Ordering Information

Part Number	Output Voltage	Packaging Type	Marking Code	Shipping Qty
UM1770Y-00	ADJ	SOT89-5	1770-00	1000pcs/7Inch Tape & Reel
UM1770Y-10	1.0V		1770-10	
UM1770Y-11	1.1V		1770-11	
UM1770Y-12	1.2V		1770-12	
UM1770Y-13	1.3V		1770-13	
UM1770Y-14	1.4V		1770-14	
UM1770Y-15	1.5V		1770-15	
UM1770Y-16	1.6V		1770-16	
UM1770Y-17	1.7V		1770-17	
UM1770Y-18	1.8V		1770-18	
UM1770Y-19	1.9V		1770-19	
UM1770Y-20	2.0V		1770-20	
UM1770Y-21	2.1V		1770-21	
UM1770Y-22	2.2V		1770-22	
UM1770Y-23	2.3V		1770-23	
UM1770Y-24	2.4V		1770-24	
UM1770Y-25	2.5V		1770-25	
UM1770Y-26	2.6V		1770-26	
UM1770Y-27	2.7V		1770-27	
UM1770Y-28	2.8V		1770-28	
UM1770Y-29	2.9V		1770-29	
UM1770Y-30	3.0V		1770-30	
UM1770Y-31	3.1V		1770-31	
UM1770Y-32	3.2V		1770-32	
UM1770Y-33	3.3V		1770-33	
UM1770Y-34	3.4V		1770-34	
UM1770Y-35	3.5V		1770-35	
UM1770Y-36	3.6V		1770-36	
UM1770Y-37	3.7V		1770-37	
UM1770Y-38	3.8V		1770-38	
UM1770Y-39	3.9V		1770-39	
UM1770Y-40	4.0V		1770-40	

Ordering Information (Continued)

Part Number	Output Voltage	Packaging Type	Marking Code	Shipping Qty
UM1770DA-00	ADJ	DFN6 2.0×2.0	AFJ	3000pcs/7Inch Tape & Reel
UM1770DA-10	1.0V		AAS	
UM1770DA-11	1.1V		AAT	
UM1770DA-12	1.2V		AAC	
UM1770DA-13	1.3V		AAD	
UM1770DA-14	1.4V		AAU	
UM1770DA-15	1.5V		AAJ	
UM1770DA-16	1.6V		AFE	
UM1770DA-17	1.7V		AFF	
UM1770DA-18	1.8V		AAK	
UM1770DA-19	1.9V		AFG	
UM1770DA-20	2.0V		AFH	
UM1770DA-21	2.1V		AFK	
UM1770DA-22	2.2V		AFL	
UM1770DA-23	2.3V		AFN	
UM1770DA-24	2.4V		AFP	
UM1770DA-25	2.5V		AAN	
UM1770DA-26	2.6V		AFQ	
UM1770DA-27	2.7V		AFR	
UM1770DA-28	2.8V		AAQ	
UM1770DA-29	2.9V		AFS	
UM1770DA-30	3.0V		AAR	
UM1770DA-31	3.1V		AFT	
UM1770DA-32	3.2V		AFU	
UM1770DA-33	3.3V		AAV	
UM1770DA-34	3.4V		AFV	
UM1770DA-35	3.5V		AAZ	
UM1770DA-36	3.6V		AFZ	
UM1770DA-37	3.7V		AGL	
UM1770DA-38	3.8V		AGN	
UM1770DA-39	3.9V		AGP	
UM1770DA-40	4.0V		AGQ	

Ordering Information (Continued)

Part Number	Output Voltage	Packaging Type	Marking Code	Shipping Qty
UM1770S-00	ADJ	SOT23-5	5CT	3000pcs/7Inch Tape & Reel
UM1770S-10	1.0V		5JA	
UM1770S-11	1.1V		5JB	
UM1770S-12	1.2V		5J2	
UM1770S-13	1.3V		5J3	
UM1770S-14	1.4V		5J4	
UM1770S-15	1.5V		5J5	
UM1770S-16	1.6V		5J6	
UM1770S-17	1.7V		5J7	
UM1770S-18	1.8V		5J8	
UM1770S-19	1.9V		5J9	
UM1770S-20	2.0V		5NA	
UM1770S-21	2.1V		5NB	
UM1770S-22	2.2V		5N2	
UM1770S-23	2.3V		5N3	
UM1770S-24	2.4V		5N4	
UM1770S-25	2.5V		5N5	
UM1770S-26	2.6V		5N6	
UM1770S-27	2.7V		5N7	
UM1770S-28	2.8V		5N8	
UM1770S-29	2.9V		5N9	
UM1770S-30	3.0V		5PA	
UM1770S-31	3.1V		5PB	
UM1770S-32	3.2V		5HP	
UM1770S-33	3.3V		5CU	
UM1770S-34	3.4V		5P4	
UM1770S-35	3.5V		5P5	
UM1770S-36	3.6V		5P6	
UM1770S-37	3.7V		5P7	
UM1770S-38	3.8V		5P8	
UM1770S-39	3.9V		5P9	
UM1770S-40	4.0V		5PC	

Absolute Maximum Ratings (Note 1)

Symbol	Parameter		Value	Unit
V _{IN}	Supply Voltage on VIN Pin		-0.3 to +7.5	V
V _{SHDN}	Voltage on SHDN Pin		-0.3 to +7.5	V
V _{OUT}	Voltage on VOUT Pin		-0.3 to +7.5	V
V _{FB}	Voltage on FB Pin		-0.3 to +7.5	V
T _A	Operating ambient temperature		-40 to +85	°C
T _J	Operating Junction Temperature (Note 2, 3)		-40 to +125	°C
T _{STG}	Storage Temperature Range		-65 to +150	°C
T _L	Lead Temperature for Soldering 10 Seconds		+260	°C
P _D (Note 4)	Power Dissipation @ 25 °C	DFN6 2.0×2.0	0.9	W
		SOT89-5	1.5	
		SOT23-5	0.47	
θ _{JA}	Package Thermal Resistance	DFN6 2.0×2.0	110	°C/W
		SOT89-5	66	
		SOT23-5	215	

Note 1: Absolute Maximum Ratings are those values beyond which the life of a device may be impaired.

Note 2: Specifications over the -40 °C to 125 °C operating junction temperature range are assured by design, characterization and correlation with statistical process controls.







Note 3: This IC includes over-temperature protection that is intended to protect the device during momentary overload conditions. Junction temperature will exceed 125 °C when over-temperature protection is active. Continuous operation above the specified maximum operating junction temperature may impair device reliability.

Note 4: The maximum allowable power dissipation of any T_A (ambient temperature) is $P_{D\text{MAX}} = (T_{J\text{MAX}} - T_A) / \theta_{JA}$. Exceeding the maximum allowable power dissipation will result in excessive die temperature and the regulator will go into thermal shutdown.

Electrical Characteristics
 $V_{IN} = V_{OUT} + 1V$ ($V_{IN} \geq 2.5V$), $C_{IN} = C_{OUT} = 1.0\mu F$, $T_A = 25^\circ C$, unless otherwise noted.







Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{IN}	Input Voltage Range		2.5		6.0	V
V_{UVLO}	Input Under Voltage Lockout	V_{IN} Falling	1.8		2.4	V
I_Q	Operating Quiescent Current	$V_{IN}=4.2V, I_{OUT}=0mA$		92	140	μA
		$V_{IN}=4.2V, I_{OUT}=500mA$		250	300	
I_{SHDN}	Shutdown Leakage Current				1	μA
I_{OUT}	Output Current		500			mA
	Output Voltage Accuracy	$1mA \leq I_{OUT} \leq 500mA, T_A = -25^\circ C$	-2		+2	%
V_{FB}	Feedback Voltage		0.98	1.0	1.02	V
ΔV_{DO}	Dropout Voltage	$I_{OUT}=500mA, 2.5V \leq V_{OUT}$		220	320	mV
I_{LIMIT}	Output Current Limit	$V_{IN} \geq 2.5V$	650			mA
t	Startup Time Response	$R_L=68\Omega, C_{OUT}=1.0\mu F$		40		μs
V_{IL}	$\overline{SHDN}$ Input Low Voltage	$2.5V \leq V_{IN} \leq 6.0V$			0.4	V
V_{IH}	$\overline{SHDN}$ Input High Voltage	$2.5V \leq V_{IN} \leq 6.0V$	2.0			V
	$\overline{SHDN}$ Input Current	$\overline{SHDN}=V_{IN}$ or GND	-1		+1	μA
T_{SHDN}	Thermal-Shutdown Temperature			160		$^\circ C$
ΔT_{SHDN}	Thermal-Shutdown Hysteresis			25		$^\circ C$
	Line Regulation	$V_{OUT}+1V \leq V_{IN} \leq 6.0V$ ($2.5V \leq V_{IN}$) $I_{OUT}=10mA$		0.09		%/V
	Load Regulation	$V_{IN}=V_{OUT}+1V$ ($2.5V \leq V_{IN}$) $1mA \leq I_{OUT} \leq 500mA$		0.2		%
	Output Voltage Noise	10Hz to 100kHz, $C_{IN}=1.0\mu F$, $I_{OUT}=100mA$	Fixed Output, $V_{OUT}=1.0V$		90	μV_{RMS}
			Adjustable Output, $V_{OUT}=1.0V$		60	
			Adjustable Output, $V_{OUT}=3.3V$		194	
			Adjustable Output, $V_{OUT}=5.0V$		305	
PSRR	Power Supply Ripple Rejection	$V_{IN}=V_{OUT}+1V$ $I_{OUT}=10mA$	f=100Hz		65	dB
			f=1kHz		60	
			f=10kHz		45	

Typical Characteristics (shown for 1.1V output option)
($C_{IN}=1.0\mu F$, $C_{OUT}=1.0\mu F$, $T_A=25^\circ C$, unless otherwise specified.)



Typical Characteristics (shown for 1.1V output option) (Continued)


($C_{IN}=1.0\mu F$, $C_{OUT}=1.0\mu F$, $T_A=25^\circ C$, unless otherwise specified.)




Typical Characteristics (shown for 1.1V output option) (Continued)

($C_{IN}=1.0\mu F$, $C_{OUT}=1.0\mu F$, $T_A=25^\circ C$, unless otherwise specified.)


Load Transient Response




Line Transient Response



Startup Waveform



Shutdown Waveform



Pin Function

SHDN: Shutdown, Active Low. This pin is used to put the UM1770 into shutdown. The SHDN pin cannot be left floating and must be tied to the input pin if not used.

GND: Ground and Heat Sink. Solder to a ground plane or large pad to maximize heat dissipation.

VIN: Power for UM1770 and Load. Power is supplied to the devices through the VIN pin. The VIN pin should be locally bypassed to ground if the UM1770 series are more than a few inches away from another source of bulk capacitance.

VOUT: Voltage Regulated Output. The VOUT pin supplies power to the load. A minimum output capacitor of 1μF is required to ensure stability. Larger output capacitors may be required for applications with large transient loads to limit peak voltage transients.

NC: Not Connected.

FB: Output voltage feedback. This terminal is used to set the output voltage.

Output Voltage Setting

The output voltage of the UM1770 adjustable regulator is programmed using an external resistor divider as shown in Figure 2. The output voltage is calculated using:

$$V_{OUT} = V_{FB} \left(1 + \frac{R1}{R2} \right)$$

Where: $V_{FB}=1.00V$ (Typ) (the internal reference voltage)

Resistors R1 and R2 should be chosen for approximately 3-5μA divider current. Lower value resistors can be used but offer no inherent advantage and waste more power. Higher values should be avoided, as leakage currents at FB increase the output voltage error. The recommended design procedure is to choose $R2=200k\Omega$ to set the divider current at 5μA and then calculate R1 using:

$$R1 = \left(\frac{V_{OUT}}{V_{FB}} - 1 \right) \times R2$$

Where: $V_{FB}=1.00V$ (Typ).

Typical Application Circuit




Figure 1. Fixed Output Voltage Application Circuit





Figure 2. Adjustable Output Voltage Application Circuit


Package Information

SOT89-5

Outline Drawing



Land Pattern




DFN6 2.0×2.0

Outline Drawing


DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	0.55	-	0.80	0.022	-	0.031
A1	0.00	-	0.05	0.000	-	0.002
A3	0.20REF			0.008REF		
b	0.25	0.30	0.35	0.010	0.012	0.014
D	1.924	2.00	2.076	0.076	0.079	0.082
D2	1.35	-	1.75	0.053	-	0.069
E	1.924	2.00	2.076	0.076	0.079	0.082
E2	0.65	-	1.06	0.026	-	0.042
e	0.65BSC			0.026BSC		
L	0.224	-	0.45	0.009	-	0.018

Land Pattern


	NOTES: 1. Compound dimension: 2.00×2.00; 2. Unit: mm; 3. General tolerance $\pm 0.05\text{mm}$ unless otherwise specified; 4. The layout is just for reference.
---	--

SOT23-5


Outline Drawing



Land Pattern



Packing Information



Part Number	Package Type	Carrier Width (W)	Pitch (P0)	Pitch (P1)	Reel Size (D)	PIN 1 Quadrant
UM1770Y-xx	SOT89-5	12 mm	4 mm	8 mm	180 mm	Q3
UM1770DA-xx	DFN6 2.0×2.0	8 mm	4 mm	4 mm	180 mm	Q1
UM1770S-xx	SOT23-5	8 mm	4 mm	4 mm	180 mm	Q3

GREEN COMPLIANCE

Union Semiconductor is committed to environmental excellence in all aspects of its operations including meeting or exceeding regulatory requirements with respect to the use of hazardous substances. Numerous successful programs have been implemented to reduce the use of hazardous substances and/or emissions.

All Union components are compliant with the RoHS directive, which helps to support customers in their compliance with environmental directives. For more green compliance information, please visit:

http://www.union-ic.com/index.aspx?cat_code=RoHSDeclaration

IMPORTANT NOTICE

The information in this document has been carefully reviewed and is believed to be accurate. Nonetheless, this document is subject to change without notice. Union assumes no responsibility for any inaccuracies that may be contained in this document, and makes no commitment to update or to keep current the contained information, or to notify a person or organization of any update. Union reserves the right to make changes, at any time, in order to improve reliability, function or design and to attempt to supply the best product possible.