

扁平式、600mA、集成电感的同步降压转换器

UM3502QA QFN24 4.0×4.0

描述

UM3502QA 是一款完整的电源转换解决方案，只需两个低成本 MLCC 陶瓷电容，电感、MOSFET、同步整流器和控制电流都集成在一个 4mm×4mm×1.05mm 的微型 QFN 封装中。UM3502Q 旨在简化设计并最大限度地减少布局限制。在空间受限的应用中，它是取代较低效率的 LDO 以提高效率的理想选择。UM3502QA 能够在 2.5V 至 5.5V 宽输入电压范围内提供 600mA 输出电流。

UM3502QA 是一款采用 PWM 同步整流的高效降压 DC-DC 转换器。UM3502QA 可在电感器电流较低时自动关闭同步整流器，并在轻负载条件下进入脉冲跳频模式，以提高效率。在正常负载条件下，工作频率设定为 1.2MHz。UM3502QA 在 EN 引脚拉低时进入关断模式，工作电流低于 0.1μA。


应用

- 蜂窝电话和智能手机
- MCU、DSP 和 FPGA 核心电源
- 无线和 DSL 调制解调器
- 便携式游戏机和乐器
- PDA、GPS
- 蓝牙耳机
- 电池供电设备

特性


- 超小型 QFN 4.0×4.0×1.05 封装
- 集成电感
- 无需肖特基二极管
- 效率高达 90%
- 600mA 输出电流
- 0.6V 最小输出电压
- 2.5V 至 5.5V 输入电压范围
- 关机电流 <1μA
- 脉冲跳频模式
- 过温保护

典型应用电路




* C_A 和 C_{FF} 是可选项。

轻载效率



Pin Configurations

Top View



Pin Description

Pin Number	Symbol	Function
1-3, 24	V _{OUT}	Regulated output voltage. Must be closely placed a 10μF or greater ceramic capacitor. These pins are connected together inside the package.
4, 9, 14	NC	Not connected.
5-8	NC(SW)	Not connected—These pins are internally connected to the common switching node of the internal MOSFETs. NC(SW) pins are not to be electrically connected to any external signal, ground, or voltage. However, they must be soldered to the PCB.
10	AGND	Analog ground. This is the ground for the internal control circuitry, and the ground return for external feedback voltage divider. It must be connected to the quiet point of the ground.
21-23	PGND	Power ground. Connect this pin to the ground electrode of the input and output filter capacitors closely.
11	NC(PGND)	This pin has been connected with PGND inside the package. No other connection is needed in use.
12	FB	Feedback input pin. Connect FB to the center point of the external resistor divider.
13	EN	Chip enable control. Drive EN above 1.0V to turn on the part. Drive EN below 0.4V to turn it off. Do not leave EN floating.
15	AV _{IN}	Input power supply for the controller circuitry. Connect to V _{IN} at a quiet point. This pin is usually connected to the positive electrode of C _{IN} .
16-20	PV _{IN}	Power input for the MOSFET switches. Must be closely decoupled to GND with a 4.7μF or greater ceramic capacitor. These pins are connected together inside the package.

Ordering Information

Part Number	Packaging Type	Marking Code	Shipping Qty
UM3502QA	QFN24 4.0×4.0	3502	3000pcs/13Inch Tape & Reel

Absolute Maximum Ratings (Note 1)

Symbol	Parameter	Value	Unit
V_{IN}, V_{OUT}	Input and Output Voltages	-0.3 to +6.0	V
V_{EN}, V_{FB}	EN, FB Voltages	-0.3 to $V_{IN}+0.3$	V
V_{SW}	SW Voltage	-0.3 to $V_{IN}+0.3$	V
I_{SW}	Peak SW Sink and Source Current	1.5	A
T_O	Operating Temperature	-40 to +85	°C
T_{STG}	Storage Temperature Range	-65 to +150	°C
T_{REFLOW}	Reflow Temperature, MSL3 JEDEC J-STD-020C, 10 Sec	260	°C

Note 1: Stresses greater than those listed under Maximum Ratings may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

Electrical Characteristics (Note 2)

($V_{IN}=V_{EN}=3.6V$, $T_A=+25\text{ °C}$, $C_{IN}=4.7\mu F$, $C_{OUT}=10\mu F$, unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{IN}	Input Voltage Range		2.5		5.5	V
V_{OUT}	Output Voltage Range		0.6		5	V
$I_{O(max)}$	Maximum Output Current	$V_{IN}\geq 3V$, $V_{OUT}=1.8V$	600			mA
		$V_{IN}=2.5V$, $V_{OUT}=1.8V$	300			
I_Q (Active)	Input DC Supply Current (Active Mode)	$V_{FB}=0.6V$, $I_{LOAD}=0A$		60		μA
I_Q (Shutdown)	Input DC Supply Current (Shutdown Mode)	$V_{EN}=0V$		0.1	1.0	μA
V_{FB}	Feedback Voltage		0.5880	0.6000	0.6120	V
		$T_A=-40\sim 85\text{ °C}$	0.5830	0.6000	0.6150	
I_{FB}	FB Input Bias Current	$V_{FB}=0.65V$			± 30	nA
	Reference Voltage Line Regulation	$2.5V\leq V_{IN}\leq 5.5V$, $V_{OUT}=V_{FB}$ ($R2=0$)		0.11	0.40	%/V
	Output Voltage Line Regulation	$2.5V\leq V_{IN}\leq 5.5V$, $I_{OUT}=10mA$		0.11	0.40	%/V
	Output Voltage Load Regulation	$100mA\leq I_{OUT}\leq 600mA$		0.0015		%/mA
f	Oscillator Frequency	$V_{FB}=0.6V$ or $V_{OUT}=100\%$		1.2		MHz
$R_{DS(ON)}$	$R_{DS(ON)}$ of P-CH MOSFET	$V_{IN}=3.6V$, $I_{SW}=100mA$		0.45	0.55	Ω
	$R_{DS(ON)}$ of N-CH MOSFET	$V_{IN}=3.6V$, $I_{SW}=-100mA$		0.30	0.40	Ω
	Internal Inductor DCR			0.18	0.23	Ω
I_P	Peak Inductor Current	$V_{IN}=3.0V$, $V_{FB}=0.5V$ or $V_{OUT}=90\%$, Duty Cycle<35%	0.90	1.20	1.60	A

Electrical Characteristics (Continued)


($V_{IN}=V_{EN}=3.6V$, $T_A=+25^{\circ}C$, $C_{IN}=4.7\mu F$, $C_{OUT}=10\mu F$, unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
I_{SWL}	SW Leakage	$V_{EN}=0V$, $V_{IN}=5V$, $V_{SW}=0V$ or $5V$		± 0.01	± 1	μA
V_H	EN High-Level Threshold	$-40^{\circ}C \leq T_A \leq 85^{\circ}C$	1.0			V
V_L	EN Low-Level Threshold	$-40^{\circ}C \leq T_A \leq 85^{\circ}C$			0.4	V
I_{ENL}	EN Leakage Current			± 0.1	± 1	μA
$\eta_{(max)}$	Max. Efficiency	$V_{IN}=3.6V$, $V_{OUT}=2.5V$		90		%
	Thermal Shutdown Temperature			160		$^{\circ}C$
	Thermal Shutdown Trip Point Hysteresis			25		$^{\circ}C$

Note2: 100% production test at $+25^{\circ}C$. Specifications over the temperature range are guaranteed by design and characterization.







Typical Performance Characteristics

($V_{IN}=3.6V$, $V_{OUT}=1.8V$, $C_{IN}=4.7\mu F$, $C_{OUT}=10\mu F$, $T_A=+25^{\circ}C$, unless otherwise noted.)



Typical Performance Characteristics (Continued)


($V_{IN}=3.6V$, $V_{OUT}=1.8V$, $C_{IN}=4.7\mu F$, $C_{OUT}=10\mu F$, $T_A=+25^\circ C$, unless otherwise noted.)




Typical Performance Characteristics (Continued)

($V_{IN}=3.6V$, $V_{OUT}=1.8V$, $C_{IN}=4.7\mu F$, $C_{OUT}=10\mu F$, $T_A=+25^\circ C$, unless otherwise noted.)


Pulse Skipping Mode Operation
($I_{OUT}=1mA$)




Normal Operation
($I_{OUT}=100mA$)




Ripple and HF Noise
($I_{OUT}=300mA$)




Ripple and HF Noise
($I_{OUT}=300mA$)



Ripple and HF Noise
($I_{OUT}=300mA$)




Ripple and HF Noise
($I_{OUT}=300mA$)




Typical Performance Characteristics (Continued)

($V_{IN}=3.6V$, $V_{OUT}=1.8V$, $C_{IN}=4.7\mu F$, $C_{OUT}=10\mu F$, $T_A=+25^\circ C$, unless otherwise noted.)


Ripple
($I_{OUT}=20mA$)




Ripple
($I_{OUT}=20mA$)



Start-up from Shutdown
($I_{OUT}=300mA$)



Block Diagram



Function Description

Integrated Inductor

The UM3502QA utilizes a low loss, multilayer inductor. The DCR of the integrated inductor is 180mΩ and the inductor is about 2.2μH. The use of an internal inductor localizes the noise associated with the output loop currents. The proprietary integrated inductor construction reduces the area of the converter's large current loop that can reduce the radiated noise coupled into the traces of the circuit board. Furthermore, the package layout is optimized to reduce the electrical path length for the AC ripple currents that are a major source of radiated emissions from DC-DC converters. The integrated inductor significantly reduces parasitic effects that can harm loop stability, and makes layout very simple. All these lead to lower output noise and fewer influences on the input power.

Current Mode PWM Control and Current Limit

The UM3502QA uses constant frequency, current mode step-down architecture. Both the main (P-channel MOSFET) and synchronous (N-channel MOSFET) switches are internal. From the block diagram, a comparator ICOMP is used to realize current limit protection. Lossless current sensing converts the peak current signal to a voltage to sum in with the internal slope compensation. This summed signal is compared to the error amplifier output to provide a peak current control command for the PWM. The cycle-by-cycle current limit is set at 1200mA (typical). During normal operation, the internal top power MOSFET is turned on each cycle when the oscillator sets the RS latch, and turned off when the current comparator ICOMP, resets the RS latch. The peak inductor current at which ICOMP resets the RS latch, is controlled by the output of error amplifier EA. When the load current increases, it causes a slight decrease in the feedback voltage, FB, relative to the 0.6V reference, which in turn, causes the EA amplifier's output voltage to increase until the average inductor current matches the new load current. While the top MOSFET is off, the bottom MOSFET is turned on until either the inductor current starts to reverse, as indicated by the current reversal comparator I_{ZERO}, or the beginning of the next clock cycle.

When the output is shorted to ground, the inductor current may exceed the maximum inductor peak current if not allowed enough time to decay. To prevent the inductor current from running away, the bottom N-channel MOSFET is allowed to stay on for more than one cycle, thereby allowing the inductor current time to decay.

Pulse Skipping Mode Operation

At very light loads, the UM3502QA automatically enters Pulse Skipping Mode. In the Pulse Skipping Mode, the inductor current may reach zero or reverse on each pulse. The PWM control loop will automatically skip pulses to maintain output regulation. The bottom MOSFET is turned off by the current reversal comparator, I_{ZERO}, and the switch voltage will ring. This is discontinuous mode operation, and is normal behavior for the switching regulator.

Enable

The EN pin provides a means to shut down the converter or enable normal operation. A logic low will disable the converter and cause it to shut down. A logic high will enable the converter into normal operation. In shutdown mode, the device quiescent current will be less than 1μA. The EN pin must not be left floating.

Thermal Shutdown

When excessive power is dissipated in the chip, the junction temperature rises. Once the junction temperature exceeds the thermal shutdown temperature, the thermal shutdown circuit turns off the converter output voltage thus allowing the device to cool. When the junction temperature decreases by 25 °C, the device will go through the normal startup process.

Applications Information

Output Voltage Setting

The output voltage is set by a resistive divider according to the following formula:

$$V_{OUT} = 0.6V \left(1 + \frac{R2}{R1} \right)$$

The value of R1 should be less than 500kΩ, so that the input current on FB pin can reduce its influence on the accuracy of the output voltage. The C_{FF} capacitor is used to compensate the gain of the loop for improved stability and the value of the capacitor is usually 4.7pF to 22pF, but it is optional.

Capacitor Selection

The input capacitor reduces the surge current drawn from the input and switching noise from the device. The input capacitor impedance at the switching frequency shall be less than input source impedance to prevent high frequency switching current passing to the input. Ceramic capacitors with X5R or X7R dielectrics are highly recommended because of their low ESR and small temperature coefficients. For most applications, a 4.7 μF capacitor is sufficient.

The AV_{IN} is separate from the PV_{IN} in the chip. A C_A capacitor can be used to decouple alone. The AV_{IN} can also be directly connected to the positive electrode of the C_{IN} to decouple.

The output capacitor keeps output voltage ripple small and ensures regulation loop stable. The output capacitor impedance shall be low at the switching frequency. Ceramic capacitor with X5R or X7R dielectrics are recommended. For most applications, a 10 μF capacitor is sufficient. For smaller output voltage ripple, you can choose a bigger output capacitor.

Exposed Metal on the Bottom of the Package

The UM3502QA utilizes the lead frame as part of the electrical circuit. The lead frame offers many advantages in thermal performance, in reduced electrical lead resistance and in overall foot print. However, it does require some special considerations.

As part of the package assembly process, lead frame construction requires that for mechanical support, some of the lead-frame metal be exposed at the point where wire-bond or internal passives are attached. This results in several small pads being exposed on the bottom of the package.

The “grayed-out” area in Figure 1 represents the area that should be clear of any metal (traces, vias, or planes) on the top layer of the PCB.




Figure 1. Exposed Metal of the Package

Layout Guidance

The package of the UM3502QA has been optimized that makes it easy for layout. It is an ideal choice to be used to replace less efficient LDO to achieve improved efficiency in space restricted applications.

When laying out the PC board, the following suggestions should be taken to ensure higher performance of the UM3502QA.


1. PCB with at least two planes is recommended. Keep the GND plane under the converter as complete as possible.
2. Connect the input capacitor C_{IN} to the PV_{IN} and PGND pins, the output capacitor C_{OUT} to the V_{OUT} and PGND pins as closely as possible to get good power filter effect.
3. The power traces, including the PGND trace, the PV_{IN} trace and V_{OUT} trace should be kept short, direct and wide to allow large current flow.
4. Connect AV_{IN} and AGND to a quiet point. The AGND pin is usually connected to the GND plane by vias. The AV_{IN} pin should be directly connected to the positive electrode of C_{IN} . A 0.1 μ F capacitor can also be used to decouple for better performance.
5. Keep the SW pin away from the sensitive FB node. This pin should also not be electrically connected to any external signal, ground, or voltage.
6. Do not trace signal line under the chip.

Package Information


UM3502QA: QFN24 4.0×4.0

Outline Drawing


DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	1.00	1.05	1.10	0.039	0.041	0.043
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	0.152REF			0.006REF		
b	0.20	0.25	0.30	0.008	0.010	0.012
D	3.90	4.00	4.10	0.154	0.157	0.161
E	3.90	4.00	4.10	0.154	0.157	0.161
D1	0.40	0.50	0.60	0.016	0.020	0.024
E1	0.25	0.35	0.45	0.010	0.014	0.018
D2	0.75	0.85	0.95	0.030	0.033	0.037
E2	1.92	2.02	2.12	0.076	0.080	0.083
D3	1.37	1.47	1.57	0.054	0.058	0.062
E3	0.45	0.55	0.65	0.018	0.022	0.026
D4	1.37	1.47	1.57	0.054	0.058	0.062
E4	0.67	0.77	0.87	0.026	0.030	0.034
D5	0.84	0.94	1.04	0.033	0.037	0.041
E5	0.25	0.35	0.45	0.010	0.014	0.018
D6	0.10	0.20	0.30	0.004	0.008	0.012
E6	0.25	0.35	0.45	0.010	0.014	0.018
e	0.40	0.50	0.60	0.016	0.020	0.024
H	0.125REF			0.005REF		
H1	0.25REF			0.010REF		
K	0.20	0.30	0.40	0.008	0.012	0.016
K1	0.25	0.35	0.45	0.010	0.014	0.018
K2	0.25	0.35	0.45	0.010	0.014	0.018
K3	0.25	0.35	0.45	0.010	0.014	0.018
L	0.25	0.30	0.35	0.010	0.012	0.014
M	0.28	0.38	0.48	0.011	0.015	0.019
M1	0.60	0.70	0.80	0.024	0.028	0.031
M2	0.28	0.38	0.48	0.011	0.015	0.019
M3	0.53	0.63	0.73	0.021	0.025	0.029
M4	0.33	0.43	0.53	0.013	0.017	0.021



Top View




Bottom View



Side View

Land Pattern



Tape and Reel Orientation



GREEN COMPLIANCE

Union Semiconductor is committed to environmental excellence in all aspects of its operations including meeting or exceeding regulatory requirements with respect to the use of hazardous substances. Numerous successful programs have been implemented to reduce the use of hazardous substances and/or emissions.

All Union components are compliant with the RoHS directive, which helps to support customers in their compliance with environmental directives. For more green compliance information, please visit:

http://www.union-ic.com/index.aspx?cat_code=RoHSDeclaration

IMPORTANT NOTICE

The information in this document has been carefully reviewed and is believed to be accurate. Nonetheless, this document is subject to change without notice. Union assumes no responsibility for any inaccuracies that may be contained in this document, and makes no commitment to update or to keep current the contained information, or to notify a person or organization of any update. Union reserves the right to make changes, at any time, in order to improve reliability, function or design and to attempt to supply the best product possible.