

## 单通道ESD保护二极管

UM5055 SOD523

### 描述

UM5055 ESD保护二极管设计用于取代手机、笔记本电脑和PDA等便携式应用中的MLV。与MLV相比，该器件内置可传导高瞬态电流的大截面积结，具有板级保护的完美电气特性，例如快速响应时间、较低的工作电压、较低的钳位电压和无器件劣化。

UM5055 ESD保护二极管可保护敏感的半导体元件免受静电放电 (ESD) 和其他瞬态电压事件的损坏或破坏。UM5055采用SOD523封装，工作电压为5 V。

在阵列不实用的应用中，设计人员能够灵活地使用该器件保护单向线路。此外，在电路板空间有限的应用中，该器件可采用分散布置的布局方案。该器件可满足IEC 61000-4-2标准的第4级静电抗扰度要求： $\pm 15\text{kV}$  空气间隙放电和  $\pm 8\text{kV}$  接触放电。

### 应用


- 手机听筒及配件
- 基于微处理器的设备
- PDA
- 笔记本电脑、台式机和服务
- 便携式设备
- 无线电话
- 数码相机
- 外围设备
- MP3 播放器

### 特性

- 数据线和电源线瞬态保护，符合IEC 61000-4-2标准： $\pm 15\text{kV}$ （空气间隙放电）， $\pm 8\text{kV}$ （接触放电）
- 用于便携式电子设备的小型封装
- ESD保护应用中MLV的合适替代品
- 保护一路I/O或电源线
- 低钳位电压
- 反向工作电压：5V
- 低漏电流
- 固态硅雪崩技术

### 引脚配置

### 顶部视图



## Ordering Information


Part Number	Working Voltage	Packaging Type	Channel	Marking Code	Shipping Qty
UM5055	5.0V	SOD523	1	ZF	3000pcs/7 Inch Tape & Reel

## Absolute Maximum Ratings


Rating	Symbol	Value	Unit
Peak Pulse Power ( $t_p=8/20\mu s$ )	$P_{PK}$	140	Watts
Maximum Peak Pulse Current ( $t_p=8/20\mu s$ )	$I_{PP}$	11	Amps
Lead Soldering Temperature	$T_L$	260 (10 sec.)	$^{\circ}C$
Operating Temperature	$T_J$	-55 to +125	$^{\circ}C$
Storage Temperature	$T_{STG}$	-55 to +150	$^{\circ}C$

## Symbol Definition

Parameter	Symbol
Maximum Reverse Peak Pulse Current	$I_{PP}$
Clamping Voltage @ $I_{pp}$	$V_C$
Working Peak Reverse Voltage	$V_{RWM}$
Maximum Reverse Leakage Current @ $V_{RWM}$	$I_R$
Breakdown Voltage @ $I_T$	$V_{BR}$
Test Current	$I_T$
Forward Current	$I_F$
Forward Voltage @ $I_F$	$V_F$
Peak Power Dissipation	$P_{PK}$
Max. Capacitance @ $V_R=0V$ , $f=1MHz$	$C$



Uni-Directional TVS



## Electrical Characteristics

(T=25 °C, Device for 5.0V Reverse Stand-Off Voltage)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse Stand-Off Voltage	$V_{RWM}$				5	V
Reverse Breakdown Voltage	$V_{BR}$	$I_T=1mA$	6	6.8	7.8	V
Reverse Leakage Current	$I_R$	$V_{RWM}=5V, T=25\text{ °C}$			0.1	$\mu A$
Clamping Voltage	$V_C$	$I_{PP}=5A, t_p=8/20\mu s$			9.1	V
		$I_{PP}=11A, t_p=8/20\mu s$			13	
Forward Voltage	$V_F$	$I_F=10mA$		0.8		V
Junction Capacitance	$C_J$	$V_R=0V, f=1MHz$		40	55	pF
Junction Capacitance	$C_J$	$V_R=2.5V, f=1MHz$		30	40	pF

## Applications Information

### Device Connection Options

UM5055 ESD protection diode is designed to protect one data, I/O, or power supply line. The device is unidirectional and may be used on lines where the signal polarity is above ground. The cathode band should be placed towards the line that is to be protected.

### Circuit Board Layout Recommendations for Suppression of ESD

Good circuit board layout is critical for the suppression of ESD induced transients. The following guidelines are recommended:

1. Place the TVS near the input terminals or connectors to restrict transient coupling.
2. Minimize the path length between the TVS and the protected line.
3. Minimize all conductive loops including power and ground loops.
4. The ESD transient return path to ground should be kept as short as possible.
5. Never run critical signals near board edges.
6. Use ground planes whenever possible. For multilayer printed-circuit boards, use ground vias.
7. Keep parallel signal paths to a minimum.
8. Avoid running protection conductors in parallel with unprotected conductor.
9. Minimize all printed-circuit board conductive loops including power and ground loops.
10. Avoid using shared transient return paths to a common ground point.

### Matte Tin Lead Finish

Matte tin has become the industry standard lead-free replacement for SnPb lead finishes. A matte tin finish is composed of 100% tin solder with large grains. Since the solder volume on the leads is small compared to the solder paste volume that is placed on the land pattern of the PCB, the reflow profile will be determined by the requirements of the solder paste. Therefore, these devices are compatible with both lead-free and SnPb assembly techniques. In addition, unlike other lead-free compositions, matte tin does not have any added alloys that can cause degradation of the solder joint.


## Package Information

### UM5055 SOD523

#### Outline Drawing

DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	0.51	0.64	0.77	0.020	0.025	0.030
A1	0.50	0.60	0.70	0.020	0.024	0.028
b	0.25	0.30	0.35	0.010	0.012	0.014
c	0.08	-	0.15	0.003	-	0.006
D	0.70	0.80	0.90	0.028	0.031	0.035
E	1.10	1.20	1.30	0.043	0.047	0.051
E1	1.50	1.60	1.70	0.059	0.063	0.067
E2	0.20REF			0.008REF		
L	0.01	0.04	0.07	0.0004	0.002	0.003
$\theta$	7° REF			7° REF		

#### Land Pattern

	<p>NOTES:</p> <ol style="list-style-type: none"> <li>Compound dimension: 1.20×0.80;</li> <li>Unit: mm;</li> <li>General tolerance <math>\pm 0.05\text{mm}</math> unless otherwise specified;</li> <li>The layout is just for reference.</li> </ol>
---	--

#### Tape and Reel Orientation


---

---

## **GREEN COMPLIANCE**

Union Semiconductor is committed to environmental excellence in all aspects of its operations including meeting or exceeding regulatory requirements with respect to the use of hazardous substances. Numerous successful programs have been implemented to reduce the use of hazardous substances and/or emissions.

All Union components are compliant with the RoHS directive, which helps to support customers in their compliance with environmental directives. For more green compliance information, please visit:

[http://www.union-ic.com/index.aspx?cat\\_code=RoHSDeclaration](http://www.union-ic.com/index.aspx?cat_code=RoHSDeclaration)

## **IMPORTANT NOTICE**

The information in this document has been carefully reviewed and is believed to be accurate. Nonetheless, this document is subject to change without notice. Union assumes no responsibility for any inaccuracies that may be contained in this document, and makes no commitment to update or to keep current the contained information, or to notify a person or organization of any update. Union reserves the right to make changes, at any time, in order to improve reliability, function or design and to attempt to supply the best product possible.