High-Speed Isolated CAN Transceiver with ±70V Bus Fault Protection

UMISO1042H *WSOP8/WSOP16/WSSOP10*
UMISO1044H *SOP8*
UMISO1050H *DUB8/WSOP8/WSOP16/WWSOP8*

1 Description

The UMISO1042H, UMISO1044H and UMISO1050H are isolated CAN transceivers with up to ±70V CAN bus fault tolerant which are fully compatible with the ISO11898-2 standard. The devices have logic input and output buffers separated by a silicon oxide (SiO_2) insulation barrier that provides galvanic isolation of up to 7500 V_{RMS} for WWSOP package, and up to 5000 V_{RMS} for WSOP and WSSOP packages, and up to 3750 V_{RMS} for SOP and DUB packages, which provides high electromagnetic immunity and low emissions.

The UMISO1042H, UMISO1044H and UMISO1050H differ in terms of pin configuration and package type. The data rate of the devices is up to 5Mbps. The device is designed for operation in especially harsh environments that feature cross-wire, overvoltage and loss of ground protection from -70V to 70V, as well as -30V to 30V common-mode range. The devices also provide thermal protection and transmit data dominant time out function.

The UMISO1042H is available in WSOP8, WSOP16 and WSSOP10 packages. The UMISO1044H is available in SOP8 package. The UMISO1050H is available in DUB8, WSOP8, WSOP16 and WWSOP8 packages. All devices operate over a temperature range of -40℃ to 125℃.


2 Features

- Fully compatible with the ISO11898-2 standard
- I/O voltage range supports 3.3 V and 5 V microprocessors
- Date rate: up to 5Mbps
- Low loop delay: 180ns (typical)
- Integrated protection increases robustness
  - Up to 3750V_{RMS} isolation rating (SOP, DUB package)
  - Up to 5000V_{RMS} isolation rating (WSOP, WSSOP package)
  - Up to 7500V_{RMS} isolation rating (WWSOP package)
  - ±200 kV/μs typical CMTI
  - High lifetime: >40 years
- Transmit data (TXD) dominant time out function
- Bus fault protection of -70V to +70V
- Over current and over temperature protection
- Compliant with safety regulatory
  - DIN EN IEC 60747-17 (VDE 0884-17)
  - UL according to UL1577
  - IEC 61010-1 and GB 4943.1-2022
- Extended ambient temperature range: -40℃ to 125℃
- Available in SOP8, DUB8, WSOP8, WSOP16, WSSOP10 and WWSOP8 packages

3 Applications

- Industrial Automation
- HVAC Automation
- Solar Inverter
- Medical Systems
- Motor Control
- Telcom

4 Functional Block Diagrams




5 Ordering Information


Part Number	Marking Code	Isolation Rating (V_{RMS})	Package Type	Shipping Qty
UMISO1042HWS8	ISO1042HWS8	5000	WSOP8	1000pcs/13Inch Tape & Reel
UMISO1042HWSG	UMISO1042H	5000	WSOP16	1500pcs/13Inch Tape & Reel
UMISO1042HWAB	UMISO1042H	5000	WSSOP10	4000pcs/13Inch Tape & Reel
UMISO1044HS8	ISO1044HS8	3750	SOP8	3000pcs/13Inch Tape & Reel
UMISO1050HZ8	UMISO1050H	3750	DUB8	800pcs/13Inch Tape & Reel
UMISO1050HWS8	ISO1050HWS8	5000	WSOP8	1000pcs/13Inch Tape & Reel
UMISO1050HWSG	UMISO1050H	5000	WSOP16	1500pcs/13Inch Tape & Reel
UMISO1050HWWS8	ISO1050H	7500	WWSOP8	500pcs/13Inch Tape & Reel

6 Pin Configuration and Function


6.1 Pin Configuration


6.1.1 Pin Configuration of UMISO1042H







XX: Week Code
UMISO1042HWS8
WSOP8






XX: Week Code
UMISO1042HWSG
WSOP16






XX: Week Code
UMISO1042HWAB
WSSOP10


6.1.2 Pin Configuration of UMISO1044H







XX: Week Code
UMISO1044HS8
SOP8

6.1.3 Pin Configuration of UMISO1050H






XX: Week Code
UMISO1050HZ8
DUB8




XX: Week Code
UMISO1050HWS8
WSOP8



XX: Week Code
UMISO1050HWWS8
WWSOP8

6.1.3 Pin Configuration of UMISO1050H (continued)



6.2 Pin Function

Table 6-1. Pin Function

Pin Name	Function
VCCA	Power supply for isolator Logic side.
GNDA	Ground reference for isolator Logic side.
RXD	Receive data output.
TXD	Transmit data input.
NC	Not connected internally. Can be connected to supply, ground or left open on PCB.
GNDB	Ground reference for isolator Bus side.
CANL	Low-level CAN bus line.
CANH	High-level CAN bus line.
VCCB	Power supply for isolator Bus side. All VCCB pins must be powered by a common supply on PCB.

7 Specifications

7.1 Absolute Maximum Ratings (Note 1, 2)

Symbol	Parameter		Min	Typ	Max	Unit
V_{CCA}	Power supply for isolator Logic side		-0.5		6.5	V
V_{CCB}	Power supply for isolator Bus side		-0.5		6.5	V
V_{BUS}	Voltage range on CANH, CANL		-70		70	V
V_I	Voltage range on TXD (Note 3)		-0.5		V_{CCA}+0.5	V
V_O	Voltage range on RXD (Note 3)		-0.5		V_{CCA}+0.5	V
V_{ESD}	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001	All pins		±8		kV
	Contact discharge, per IEC 61000-4-2	Bus pins to GNDB		±8		kV
I_{LU}	Latch up, per JEDEC JESD78			±200		mA
T_J	Junction temperature				150	℃
T_{STG}	Storage temperature		-65		150	℃

Note 1: Operation outside the Absolute Maximum Ratings may cause permanent device damage. Absolute Maximum Ratings do not imply functional operation of the device at these or any other conditions beyond those listed under Recommended Operating Conditions. If used outside the Recommended Operating Conditions but within the Absolute Maximum Ratings, the device may not be fully functional, and this may affect device reliability, functionality, performance, and shorten the device lifetime.
Note 2: All voltage values, except differential I/O bus voltages, are with respect to ground terminal.
Note 3: Maximum voltage must not exceed 6.5 V.

7.2 Recommended Operating Conditions

Symbol	Parameter	Min	Typ	Max	Unit
V_{CCA}	Power supply for isolator Logic side	3.0		5.5	V
V_{CCB}	Power supply for isolator Bus side	4.5		5.5	V
V_{IH}	Input High Voltage (TXD)	0.7V_{CCA}			V
V_{IL}	Input Low Voltage (TXD)			0.3V_{CCA}	V
T_A	Ambient temperature	-40		125	℃

7.3 Thermal Information

Symbol	Parameter		Value	Unit
$R_{\theta JA}$	Junction to ambient thermal resistance	DUB8	70	°C/W
		SOP8	119.5	°C/W
		WSOP8	105	°C/W
		WSSOP10	99	°C/W
		WSOP16	82	°C/W
		WWSOP8	TBD	°C/W

7.4 Insulation Specifications

Symbol	Parameter	Conditions	Value				Unit
			DUB8/ SOP8	WSOP8/ WSOP16	WSSOP10	WWSOP8	
CLR	External clearance	Shortest terminal-to-terminal distance through air	4	8	8	15	mm
CPG	External creepage	Shortest terminal-to-terminal distance across the package surface	4	8	8	15	mm
DTI	Distance through the insulation	Minimum internal gap (internal clearance)	>20	>20	>20	>20	μm
CTI	Comparative tracking index	DIN EN 60112 (VDE 0303-11); IEC 60112	>600	>600	>600	>600	V
	Material group	Per IEC 60664-1	I	I	I	I	
	Overvoltage category per IEC 60664-1	Rated mains voltage ≤ 150 V_{RMS}	I-IV	I-IV	I-IV	I-IV	
		Rated mains voltage ≤ 300 V_{RMS}	I-III	I-IV	I-IV	I-IV	
		Rated mains voltage ≤ 600 V_{RMS}	N/A	I-IV	I-IV	I-IV	
		Rated mains voltage ≤ 1000 V_{RMS}	N/A	I-II	I-II	I-II	
DIN V VDE V 0884-17:2021-10 (Note 1)							
V_{IORM}	Maximum repetitive peak isolation voltage	AC voltage (bipolar)	637	1414	1414	1414	V_{PK}
V_{IOWM}	Maximum operating isolation voltage	AC voltage; time-dependent dielectric breakdown (TDDB) test	450	1000	1000	1000	V_{RMS}
		DC voltage	637	1414	1414	1414	V_{DC}
V_{IOTM}	Maximum transient isolation voltage	$V_{TEST} = V_{IOTM}$, t = 60 s (certified); $V_{TEST} = 1.2 \times V_{IOTM}$, t = 1 s (100% product test)	5300	7070	7070	10605	V_{PK}
V_{IMP}	Maximum impulse voltage	Tested in air, 1.2/50 μs waveform per IEC 62368-1,	5000	7500	7500	7500	V_{PK}
V_{IOSM}	Maximum surge isolation voltage	$V_{IOSM} \geq 1.3 \times V_{IMP}$; Tested in oil (qualification test), 1.2/50 μs waveform per IEC 62368-1	6500	10000	10000	10000	V_{PK}

7.4 Insulation Specifications (Continued)

Symbol	Parameter	Conditions	Value				Unit
			DUB8/ SOP8	WSOP8/ WSOP16	WSSOP10	WWSOP8	
q_{pd}	Apparent charge (Note 2)	Method a, after input/output safety test of the subgroup 2/3, $V_{ini} = V_{IOTM}$, t_{ini} = 60 s; $V_{pd(m)} = 1.2 \times V_{IORM}$, t_m = 10 s	≤5	≤5	≤5	≤5	pC
		Method a, after environmental test of the subgroup 1, $V_{ini} = V_{IOTM}$, t_{ini} = 60 s; $V_{pd(m)} = 1.3 \times V_{IORM}$, t_m = 10 s	≤5	≤5	≤5	≤5	pC
		Method b, at routine test (100% production test) and preconditioning (type test) $V_{ini} = 1.2 \times V_{IOTM}$, t_{ini} = 1 s; $V_{pd(m)} = 1.875 \times V_{IORM}$ (for reinforced devices) or $V_{pd(m)} = 1.5 \times V_{IORM}$ (for basic devices), t_m = 1 s (method b1) or $V_{pd(m)} = V_{ini}$, $t_m = t_{ini}$ (method b2)	≤5	≤5	≤5	≤5	pC
C_{IO}	Barrier capacitance, input to output (Note 3)	V_{IO} = 0.4 × sin (2πft), f = 1 MHz	1.0	1.0	1.0	1.0	pF
R_{IO}	Isolation resistance (Note 3)	V_{IO} = 500 V, T_A = 25 ℃	$>10^{12}$	$>10^{12}$	$>10^{12}$	$>10^{12}$	Ω
		V_{IO} = 500 V, 100 ℃ ≤ T_A ≤ 125 ℃	$>10^{11}$	$>10^{11}$	$>10^{11}$	$>10^{11}$	
		V_{IO} = 500 V at T_S = 150 ℃	$>10^{9}$	$>10^{9}$	$>10^{9}$	$>10^{9}$	
	Pollution degree		2	2	2	2	
UL 1577							
V_{ISO}	Maximum withstanding isolation voltage	$V_{TEST} = V_{ISO}$, t = 60s (qualification) $V_{TEST} = 1.2 \times V_{ISO}$, t = 1 s (100% production test)	3750	5000	5000	7500	V_{RMS}

Note 1: This coupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of suitable protective circuits.
Note 2: The characterization charge is discharging charge (pd) caused by partial discharge.
Note 3: Capacitance and resistance are measured with all pins on field-side and logic-side tied together.

7.5 Electrical Characteristics

7.5.1 Electrical Characteristics (Static)

T_J = -40℃ to 150℃, V_{CCA} = 3.0 V to 5.5 V, V_{CCB} = 4.5 V to 5.5 V, R_L = 60Ω, C_L = 100pF (unless otherwise noted). Typical values are at V_{CCA} = 3.3 V, V_{CCB} = 5 V, T_A = 25℃.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Power supply						
I_{CCA}	Supply current logic side	V_{TXD} = V_{CCA}, V_{CCA} = 5.0 V		1.3	3.6	mA
I_{CCA}	Supply current logic side	V_{TXD} = 0 V, V_{CCA} = 5.0 V		2.3	4.5	mA
I_{CCB}	Supply current bus side	V_{TXD} = 0 V, bus dominant, R_L = 60 Ω		48	73	mA
I_{CCB}	Supply current bus side	V_{TXD} = V_{CCA}		5.9	12	mA
$V_{CCA(UVLO)RIS}$	Rising undervoltage detection, V_{CCA}		2.6	2.7	2.9	V
$V_{CCA(UVLO)FAL}$	Falling undervoltage detection, V_{CCA}		2.4	2.6	2.7	V
$V_{CCB(UVLO)RIS}$	Rising undervoltage detection, V_{CCB}			3.75	4.5	V
$V_{CCB(UVLO)FAL}$	Falling undervoltage detection, V_{CCB}		2.4	2.6		V
CAN transmit data input; pin TXD						
V_{IH}	High-level input voltage		0.7V_{CCA}			V
V_{IL}	Low-level input voltage				0.3V_{CCA}	V
I_{IH}	High-level input current	TXD = V_{CCA}			10	uA
I_{IL}	Low-level input current	TXD = 0 V	-10			uA
C_I	Input capacitance			5	10	pF
CAN receive data output; pin RXD						
V_{OH}	High level output voltage	I_{OH} = -4mA, see figure 8-6	V_{CCA} -0.4	V_{CCA} -0.2		V
		I_{OH} = -20uA, see figure 8-6	V_{CCA} -0.1	V_{CCA}		V
V_{OL}	Low level output voltage	I_{OL} = 4mA, see figure 8-6		0.2	0.4	V
		I_{OL} = 20uA, see figure 8-6		0	0.1	V

7.5.1 Electrical Characteristics (Static) (continued)

T_J = -40℃ to 150℃, V_{CCA} = 3.0 V to 5.5 V, V_{CCB} = 4.5 V to 5.5 V, R_L = 60Ω, C_L = 100pF (unless otherwise noted). Typical values are at V_{CCA} = 3.3 V, V_{CCB} = 5 V, T_A = 25℃.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Driver						
$V_{O(DOM)}$	Dominant output voltage	TXD = 0 V; t < $t_{DTO(TXD)}$; V_{CCB} = 4.75V to 5.25V R_L = 60 Ω; pin CANH, see figure 8-1 and 8-2	2.75	3.5	4.5	V
		TXD = 0 V; t < $t_{DTO(TXD)}$; V_{CCB} = 4.75V to 5.25V R_L = 60 Ω; pin CANL, see figure 8-1 and 8-2	0.5	1.5	2.25	V
$V_{OD(DOM)}$	Dominant differential output voltage	TXD = 0V; t < $t_{DTO(TXD)}$; V_{CCB} = 4.75V to 5.25V 50 Ω ≤ R_L ≤ 65 Ω, see figure 8-1 and 8-2	1.5		3	V
		TXD = 0V; t < $t_{DTO(TXD)}$; V_{CCB} = 4.75V to 5.25V 45 Ω ≤ R_L ≤ 70 Ω, see figure 8-1 and 8-2	1.4		3.3	V
		TXD = 0V; t < $t_{DTO(TXD)}$; V_{CCB} = 4.75V to 5.25V R_L = 2240 Ω, see figure 8-1 and 8-2	1.5		5	V
$V_{O(REC)}$	Recessive output voltage	TXD = V_{CCA}; R_L = 60 Ω, see figure 8-1 and 8-2	2	2.5	3	V
$V_{OD(REC)}$	Recessive differential output voltage	TXD = V_{CCA}; R_L = open	-100		100	mV
		TXD = V_{CCA}; R_L = 60 Ω, see figure 8-1 and 8-2	-50		50	mV
$V_{OC(DOM)}$	Common-mode output voltage (Dominant)	See figure 8-7	2	2.5	3	V
$V_{OC(PP)}$	Peak-to-peak common-mode output voltage	See figure 8-7		0.3		V
$I_{OS(DOM)}$	Dominant short-circuit output current	TXD = 0 V; CANH = -15 V to 40 V; CANL = open	-100	-75		mA
		TXD = 0 V; CANL = -15 V to 40 V; CANH = open		75	100	mA
$I_{OS(REC)}$	Recessive short-circuit output current	TXD = V_{CCA}; -27 V ≤ CANH = CANL ≤ 32 V	-5		5	mA

7.5.1 Electrical Characteristics (Static) (continued)

T_J = -40℃ to 150℃, V_{CCA} = 3.0 V to 5.5 V, V_{CCB} = 4.5 V to 5.5 V, R_L = 60Ω, C_L = 100pF (unless otherwise noted). Typical values are at V_{CCA} = 3.3 V, V_{CCB} = 5 V, T_A = 25℃.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Receiver						
V_{TH}	Differential receiver threshold voltage	-30 V ≤ CANH, CANL ≤ 30 V	0.5		0.9	V
$V_{ID(DOM)}$	Receiver dominant voltage	-30 V ≤ CANH, CANL ≤ 30 V	0.9		9	V
$V_{ID(REC)}$	Receiver recessive voltage	-30 V ≤ CANH, CANL ≤ 30 V	-4		0.5	V
V_{HYS}	Differential receiver hysteresis voltage	-30 V ≤ CANH, CANL ≤ 30 V	50		300	mV
R_I	Input resistance	TXD = V_{CCA};	15	30	40	kΩ
ΔR_I	Input resistance deviation, [1 – ($R_{IN(CANH)}$ / $R_{IN(CANL)}$)] × 100 %	TXD = V_{CCA};	-3		3	%
R_{ID}	Differential input resistance	TXD = V_{CCA};	30	60	80	kΩ
C_{IN}	Common-mode input capacitance to ground			20		pF
C_{ID}	Differential input capacitance			10		pF
CMTI	Common-mode transient immunity	V_I = V_{CCA} or 0 V, V_{CM} = 1200 V, see figure 8-12	150	200		kV/μs
Thermal Protection						
$T_{J(SD)}$	Thermal shutdown threshold	Temperature rising		185		℃

7.5.2 Electrical Characteristics (Dynamic)

T_J = -40℃ to 150℃, V_{CCA} = 3.0 V to 5.5 V, V_{CCB} = 4.5 V to 5.5 V, R_L = 60Ω, C_L = 100pF (unless otherwise noted). Typical values are at V_{CCA} = 3.3 V, V_{CCB} = 5 V, T_A = 25℃.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Device switching characteristics						
$t_{PROP(LOOP1)}$	Total loop delay, driver input TXD to receiver RXD, recessive to dominant	See figure 8-8	90	180	255	ns
$t_{PROP(LOOP2)}$	Total loop delay, driver input TXD to receiver RXD, dominant to recessive	See figure 8-8	90	180	255	ns
Driver switching characteristics						
t_{PLH}	Propagation delay time, recessive to dominant output	See figure 8-4		85	110	ns
t_{PHL}	Propagation delay time, dominant to recessive output			80	110	ns
t_R	Differential output signal rise time			25	50	ns
t_F	Differential output signal fall time			35	63	ns
$t_{DTO(TXD)}$	TXD dominant time-out time	C_L = 100pF, see figure 8-9	0.8	2.6	6.5	ms
Receiver switching characteristics						
t_{PLH}	Propagation delay time, low to high level output	See figure 8-6		95	130	ns
t_{PHL}	Propagation delay time, high to low level output			93	130	ns
t_R	Output signal rise time(RXD)			2.6	6	ns
t_F	Output signal rise time(RXD)			2	6	ns
FD timing parameters, see figure 8-11						
$t_{BIT(BUS)}$	Transmitted recessive bit width	$t_{BIT(TXD)}$ = 500ns	435		530	ns
		$t_{BIT(TXD)}$ = 200ns	155		210	ns
$t_{BIT(RXD)}$	Bit time on pin RXD	$t_{BIT(TXD)}$ = 500ns	400		550	ns
		$t_{BIT(TXD)}$ = 200ns	120		220	ns
Δt_{REC}	Receiver timing symmetry	$t_{BIT(TXD)}$ = 500ns	-65		40	ns
		$t_{BIT(TXD)}$ = 200ns	-45		15	ns

8 Parameter Measurement Information




Figure 8-1. Driver Voltage, Current and Test Definitions




Figure 8-2. Bus Logic State Voltage Definitions





Figure 8-3. Driver V_{OD} with Common-Mode Loading Test Circuit

8 Parameter Measurement Information (continued)



Note 1: The input pulse is supplied by a generator having the following characteristics: PRR≤125 kHz, 50% duty cycle, t_R≤6 ns, t_F≤6 ns, Z_O = 50 Ω.

Note 2: C_L includes instrumentation and fixture capacitance within ±20%.

Figure 8-4. Driver Test Circuit and Voltage Waveforms





Figure 8-5. Receiver Voltage and Current Definitions

8 Parameter Measurement Information (continued)



Note 1: The input pulse is supplied by a generator having the following characteristics: PRR≤125 kHz, 50% duty cycle, t_R≤6 ns, t_F≤6 ns, Z_O = 50 Ω.
Note 2: C_L includes instrumentation and fixture capacitance within ±20%.

Figure 8-6. Receiver Test Circuit and Voltage Waveforms




Figure 8-7. Peak-to-Peak Output Voltage Test Circuit and Waveform




Figure 8-8. t_{LOOP} Test Circuit and Voltage Waveforms

8 Parameter Measurement Information (continued)




Figure 8-9. Dominant Time-out Test Circuit and Voltage Waveforms




Figure 8-10. Driver Short-Circuit Current Test Circuit and Waveforms

8 Parameter Measurement Information (continued)





Figure 8-11. CAN FD Timing Parameter Measurement



Note 1: C_L includes probe and jig capacitance.

Figure 8-12. Common-Mode Transient Immunity Test Circuit

9 Detailed Description

9.1 Overview

The UMISO1042H, UMISO1044H and UMISO1050H are isolated CAN transceivers which provide galvanic isolation of up to 3750 V_{RMS} (SOP, DUB package), 5000 V_{RMS} (WSOP, WSSOP package), 7500 V_{RMS} (WWSOP package) and which is fully compatible with the ISO11898-2 standard. Additionally, the device can achieve efficient and stable communication across isolation barrier with 200kV/μs CMTI and up to 5 Mbps data rate. The logic side power supply is 3.0V to 5.5V which makes the devices ideal for communication with the microcontroller in applications like solar inters, motor control and HVAC systems. The device is designed for operation in especially harsh environments that feature cross-wire, overvoltage and loss of ground protection from -70 V to 70 V, as well as -30V to 30V common-mode range. The devices also feature thermal protection and transmit data dominant time out function.

9.2 CAN Bus States

The CAN bus has two states during operation: dominant and recessive. A dominant bus state, equivalent to logic low, is when the bus is driven differentially by a driver. A recessive bus state, equivalent to a logic high, is when the bus is biased to a common mode of $V_{CCB}/2$. The host microprocessor of the CAN node will transmit and receive data via the bus lines CANH and CANL. The differential receiver converts the analog data on the bus lines into digital data which is output to pin RXD.

9.3 Device Functional Modes

Table 9-1. Driver Function Table (Note 1)

V_{CCA}	V_{CCB}	Input	TXD Low-Level Time	Outputs		Bus State
		TXD		CANH	CANL	
Power On	Power On	L	< $t_{DTO(TXD)}$	H	L	Dominant state
		L	> $t_{DTO(TXD)}$	$V_{CCB}/2$	$V_{CCB}/2$	Recessive state
		H or Open	X	$V_{CCB}/2$	$V_{CCB}/2$	Recessive state
Power On	Power Down	X	X	Z	Z	Z
Power Down	Power On	X	X	$V_{CCB}/2$	$V_{CCB}/2$	Recessive state

Note 1: X = Don't care, H = high level, L = low level, Z = high impedance.

Table 9-2. Receiver Function Table (Note 1)

$V_{ID} = V_{CANH}-V_{CANL}$	Bus State	RXD
$V_{ID} \geq 0.9V$	Dominant state	L
$0.5V < V_{ID} < 0.9V$	Indeterminate	Indeterminate
$V_{ID} \leq 0.5V$	Recessive state	H
Open	Open	H

Note 1: X = Don't care, H = high level, L = low level, Z = high impedance.

9.4 Fail-Safe Features

9.4.1 TXD dominant time-out function

A 'TXD dominant time-out' timer is started when pin TXD is set LOW. If the LOW state on pin TXD persists for longer than $t_{DTO(TXD)}$, the transmitter is disabled, releasing the bus lines to recessive state. This function prevents a hardware and/or software application failure from driving the bus lines to a permanent dominant state (blocking all network communications). The TXD dominant time-out timer is reset when pin TXD is set HIGH.

9.4.2 Overtemperature protection

The output drivers are protected against overtemperature conditions. If the operating junction temperature exceeds the shutdown junction temperature, $T_{J(SD)}$, the output drivers will be disabled until the operating junction temperature falls below $T_{J(SD)}$ and TXD becomes recessive again. Including the TXD condition ensures that output driver oscillations due to temperature drift are avoided.

10 Application Information

10.1 Typical Application





Figure 10-1. UMISO1050H Application Circuit

11 Package Information


DUB8

Outline Drawing



DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	-	-	4.85	-	-	0.194
A1	0.35	-	-	0.014	-	-
b	1.464	1.524	1.584	0.059	0.061	0.064
b1	0.355	-	0.555	0.014	-	0.022
b2	0.93	0.99	1.05	0.037	0.040	0.042
c	0.204	-	0.355	0.008	-	0.014
D	9.02	-	9.55	0.361	-	0.382
E	10.1	-	10.7	0.404	-	0.428
E1	6.37	-	6.87	0.255	-	0.275
e	2.54BSC			0.102BSC		
L	1.15	-	1.45	0.046	-	0.058
θ	0 °	-	8 °	0 °	-	8 °


Land Pattern



NOTES:
1. Unit: mm;
2. General tolerance ±0.05mm unless otherwise specified;
3. The layout is just for reference.


SOP8

Outline Drawing



DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	-	-	1.75	-	-	0.069
A1	0.00	-	0.25	0.000	-	0.010
b	0.30	-	0.51	0.012	-	0.020
c	0.15	-	0.25	0.006	-	0.010
D	4.70	4.90	5.10	0.185	0.193	0.200
E	3.70	3.90	4.10	0.148	0.154	0.164
E1	5.80	-	6.25	0.228	-	0.250
e	1.27BSC			0.050 BSC		
L	0.40	-	1.27	0.016	-	0.050
θ	0 °	-	8 °	0 °	-	8 °


Land Pattern



NOTES:
1. Unit: mm;
2. General tolerance ±0.05mm unless otherwise specified;
3. The layout is just for reference.


WSOP8

Outline Drawing



DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	-	-	2.80	-	-	0.112
A1	0.10	-	0.46	0.004	-	0.018
A2	2.18	-	2.40	0.087	-	0.096
b	0.31	-	0.51	0.012	-	0.020
c	0.15	-	0.31	0.006	-	0.012
D	5.75	5.85	5.95	0.230	0.234	0.238
E	11.25	11.50	11.75	0.450	0.460	0.470
E1	7.40	7.50	7.60	0.296	0.300	0.304
e	1.27BSC			0.050 BSC		
L	0.50	-	1.00	0.020	-	0.040
θ	0 °	-	8 °	0 °	-	8 °


Land Pattern



NOTES:
1. Unit: mm;
2. General tolerance ±0.05mm unless otherwise specified;
3. The layout is just for reference.


WSOP16

Outline Drawing



DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	-	-	2.65	-	-	0.104
A1	0.10	-	0.30	0.004	-	0.012
A2	2.25	-	2.35	0.089	-	0.093
b	0.35	-	0.43	0.014	-	0.017
c	0.24	-	0.29	0.009	-	0.011
D	10.2	10.3	10.4	0.402	0.406	0.409
E	10.1	10.3	10.5	0.398	0.406	0.413
E1	7.4	7.5	7.6	0.291	0.295	0.299
e	1.27BSC			0.050 BSC		
L	0.55	-	0.85	0.022	-	0.033
L1	1.40REF			0.060REF		
θ	0 °	-	8 °	0 °	-	8 °


Land Pattern



NOTES:
1. Unit: mm;
2. General tolerance ±0.05mm unless otherwise specified;
3. The layout is just for reference.


WSSOP10

Outline Drawing



Symbol	DIMENSIONS					
	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	-	-	1.65	-	-	0.066
A1	0.05	-	0.20	0.002	-	0.008
A2	1.35	1.40	1.45	0.054	0.056	0.058
b	0.23	-	0.31	0.009	-	0.013
c	0.20	-	0.24	0.008	-	0.009
D	3.40	3.50	3.60	0.136	0.140	0.144
E	9.30	9.50	9.70	0.372	0.380	0.388
E1	7.40	7.50	7.60	0.296	0.300	0.304
e	0.635BSC			0.0254BSC		
L	0.45	-	0.75	0.018	-	0.030
L1	1.00REF			0.040REF		
θ	0°	-	7°	0°	-	7°


Land Pattern



NOTES:
1. Unit: mm;
2. General tolerance ±0.05mm unless otherwise specified;
3. The layout is just for reference.


WWSOP8

Outline Drawing




DIMENSIONS						
Symbol	MILLIMETERS			INCHES		
	Min	Typ	Max	Min	Typ	Max
A	-	-	2.65	-	-	0.104
A1	0.10	-	0.30	0.004	-	0.012
A2	2.25	-	2.336	0.089	-	0.092
b	0.31	-	0.51	0.012	-	0.020
c	0.22	-	0.28	0.009	-	0.011
D	6.30	-	6.50	0.248	-	0.256
E	13.90	-	14.10	0.547	-	0.555
E1	17.10	-	17.40	0.673	-	0.685
e	1.27BSC			0.050 BSC		
L	0.60	-	1.10	0.024	-	0.043
L1	1.625REF			0.064REF		
θ	0 °	-	8 °	0 °	-	8 °

Land Pattern



NOTES:
1. Unit: mm;
2. General tolerance ±0.05mm unless otherwise specified;
3. The layout is just for reference.

12 Packing Information



Part Number	Package Type	Carrier Width (W)	Pitch (P0)	Pitch (P1)	Reel Size (D)	PIN 1 Quadrant
UMISO1042HWS8	WSOP8	16 mm	4 mm	16 mm	330 mm	Q1
UMISO1042HWSG	WSOP16	16 mm	4 mm	12 mm	330 mm	Q1
UMISO1042HWAB	WSSOP10	16 mm	4 mm	8 mm	330 mm	Q2
UMISO1044HS8	SOP8	12 mm	4 mm	8 mm	330 mm	Q1
UMISO1050HZ8	DUB8	24 mm	4 mm	16 mm	330 mm	Q1
UMISO1050HWS8	WSOP8	16 mm	4 mm	16 mm	330 mm	Q1
UMISO1050HWSG	WSOP16	16 mm	4 mm	12 mm	330 mm	Q1
UMISO1050HWWS8	WWSOP8	16 mm	4 mm	24 mm	330 mm	Q1

GREEN COMPLIANCE

Union Semiconductor is committed to environmental excellence in all aspects of its operations including meeting or exceeding regulatory requirements with respect to the use of hazardous substances. Numerous successful programs have been implemented to reduce the use of hazardous substances and/or emissions.
All Union components are compliant with the RoHS directive, which helps to support customers in their compliance with environmental directives. For more green compliance information, please visit:
https://www.union-ic.com/Quality.html

IMPORTANT NOTICE

The information in this document has been carefully reviewed and is believed to be accurate. Nonetheless, this document is subject to change without notice. Union assumes no responsibility for any inaccuracies that may be contained in this document, and makes no commitment to update or to keep current the contained information, or to notify a person or organization of any update. Union reserves the right to make changes, at any time, in order to improve reliability, function or design and to attempt to supply the best product possible.